Proof, Photo & Production media
PRODUCT DATASHEET

POWERED BY bestcolor technology

EFI Offset Proof Paper 9200 Semimatt

This proof paper is especially developed for offset printing. The very wide color gamut and the quality cover the paper type classes PT1 to PT3. A very low content of optical brighteners guarantees a high stability for color management (LAB-Value: 96,7 / 0,7 / -1,2).

FSC www.fsc.org FSC® C010119
The mark of responsible forestry

Description:

Semimatt coated paper
Very wide color gamut
Very good fading properties (reduced color fading)
Very low content of optical brighteners
Fast drying (Instant-dry)
Universal use
Appearance resembles offset production paper

Controlled ΔE<0,9 Consistency

Application:

Proofing
Photo
FineArt

Technical data:

Weight	200	g / m²
Thickness	230	µ
Opacity	97	%
Gloss [Tappi 75°]	60	%
L*a*b* Paper white	96,7 / 0,7 / -1,2	
Storage	15 -30	°C (40 - 60% RH)

Size

Sheet		Rolls		Core	Rolls		Core
DIN A4	(210 x 297 mm)	25,4 cm x 30 m	(10“)	3“ *)	91,4 cm x 30 m	(36“)	3“*)
SUPER A4	(241 x 340 mm)	32,9 cm x 10 m	(13“)	2“	106,7 cm x 30 m	(42“)	3“*)
DIN A3	(297 x 420 mm)	32,9 cm x 30 m	(13“)	3“*)	111,8 cm x 30 m	(44“)	3“*)
DIN A3+	(330 x 483 mm)	36,0 cm x 30 m	(14,17“)	3“*)	127,0 cm x 30 m	(50“)	3“*)
A3++	(329 x 558 mm)	43,2 cm x 30 m	(17“)	3“*)	135,0 cm x 30 m	(53,125“)	3“*)
DIN A2	(420 x 594 mm)	45,7 cm x 25 m	(18“)	2“	137,0 cm x 30 m	(54“)	3“*)
DIN A1	(594 x 841 mm)	50,8 cm x 30 m	(20“)	3“*)	152,4 cm x 30 m	(60“)	3“*)
		61,0 cm x 25 m	(24“)	2“	162,6 cm x 30 m	(64“)	3“*)
		61,0 cm x 30 m	(24“)	3“*)			

*) supplied with each two adapters 3“ to 2“ core

Tecco® living paper

Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.